

VE 8.000



cost-effective | efficient | innovative

garant VE 8.000

Our VE 8.000 slurry tanker offers excellent value for money for small business. Running on flotation tyres, the machine minimizes ground pressure in field and pasture land. Stand-out features of the 8,000 l model include the Jurop compressor, a 40 km/h axle, air brakes, the hydraulic domed gate valve as well as Walterscheid wide-angle driveshaft with cap bottom lubrication.



40 km/h axle



Domed gate valve, bracket and Kotte exact distributor

Tanks

- quality made in Germany
- 5 mm walls
- full-length frame
- fully galvanized
- recess at rear outlet ensures thorough emptying
- two DIN EN 707 baffle plates
- standard hydraulic domed gate valve on outlet is significantly less vulnerable to solid matter; offers longer service life than piston gate valves
- standard Kotte exact distributor c/w large splash guard; 12 m working width
- standard Plexiglas sight tube with sleeve for cleaning
- optional specification: Reduced tank volume to implement low profile build

Tyres and running gear

- BPW quality axles
- 120 x 120 mm box section axle, 410 x 120 brake drum
- 40 km/h axle
- parabolic spring suspension
- standard dual-line air system with automatic and load-sensitive brakes
- large choice of tyres
- genuine Jost jack, stepless height adjustment (10 t tongue load) guarantees safe storage (Health and Safety Executive directive) and is standard specification

Quality tank

Original Jost jack

Large choice of tyres



Hydraulic turbo filler



Hydraulic turbo filler under the tank

Filling systems

- PN 8400 vacuum compressor from market leader Jurop; 9,000 l/min air capacity
- optional specification: Jurop PN 10600 compressor of 11,000 l/min air capacity
- standard Walterscheid wide-angle driveshaft with cap bottom lubrication and shear bolt protection
- oil immersed air cleaner in hot-galvanized version, noise dampening and oil separator
- optional specification: Hydraulic turbo filler on suction nozzle left or right allows for higher filling rates and substantially higher filling levels, in particular when handling semi-liquid cattle slurry.
- retrofitting the turbo filler to the suction nozzle is easy
- optional specification: Hydraulic turbo filler under tank's front end for supply from left or right

Kotte slurry equipment from A to Z

VE 11.000

GARANT VE 11.000 is the slurry tanker that brings ultimate efficiency to contiguous businesses. In combination with flotation tyres, it will provide maximum crop protection at minimum risk of compaction. Excellent manoeuvrability and high value for money make this 11,000-litre machine the top selling slurry tanker in its class.



VT 14.000 with trailing hoses

Our tandem-axle tankers are the perfect alternative to the Super Einachs VE 11.000 model and are designed for owners who travel long distances on public roads. Offering capacities of 10,000 l to 19,500 l, these machines again set the benchmark in quality, featuring genuine 60 km/h BPW Boogie steer axle assemblies, forced steering, pneumatic suspension, NW 200 turbo fillers for supply from either side of the machine.

Kotte markets a comprehensive range of application equipment including 12 to 33 m trailing hoses, up to 18 m trailing shoe applicators, dribble bars at working widths of up to 33 m as well as slurry injectors. The Kotte trailing hose applicator scored best results in a DLG Focus Test.



Josef Kotte Landtechnik
GmbH & Co. KG
Malgartener Straße 10–12
D-49597 Rieste
Phone: +49 (0) 54 64/96 11–0
Fax: +49 (0) 54 64/57 35
info@kotte-landtechnik.de
www.kotte-landtechnik.de

Dealership